



TECHNICAL SPECIFICATIONS

NOVITA® 10805 – Coloured Uncoated Orange / 0601 / Yellow Glassine

FACESTOCK

Coloured Uncoated Orange

- Description** Coloured uncoated woodfree paper.
- Printing Process** Suitable for flexo, offset and letterpress.
- Applications** Promotional and advertising labels and general stationary.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	80	±2
Thickness	ILKAY 017	µm	90	±2

ADHESIVE

0601

- Description** General use permanent adhesive for papers and films. High initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.
- Shelf Life** Two years, stored at 22°C / 50% RH.

Property	Standart	Units	Value	Tolerance
Adhesion (Peel 90°/Steel)	ILKAY 003	N/25 mm	7	minimum
Loop Tack	ILKAY 001	N/25 mm	5	minimum
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Minimum service temperature		°C	+80	

LINER

Yellow Glassine

- Description** Supercalendered transparent glassine paper. Especially used for automatic labelling applications and other systems.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	62	±2
Thickness	ILKAY 017	µm	40	±2

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.