



TECHNICAL SPECIFICATIONS

NOVITA® 10103 – Gloss Coated / 0601 / CCK 125

FACESTOCK

Gloss Coated

Description Gloss coated woodfree paper.

Printing Process Suitable for printing in all types of flexo and letterpress systems, offset, screen printing and hot stamping.

Applications High resolution standart gloss label for multicolour printing; used in food and beverage industry.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	78	±2
Thickness	ILKAY 017	µm	65	±2

ADHESIVE

0601

Description General use permanent adhesive for papers and films. High initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.

Shelf Life Two years, stored at 22°C / 50% RH.

Property	Standart	Units	Value	Tolerance
Adhesion (Peel 90°/Steel)	ILKAY 003	N/25 mm	7	minimum
Loop Tack	ILKAY 001	N/25 mm	5	minimum
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Minimum service temperature		°C	+80	

LINER

CCK 125

Description Good dimensional stability and layflatness, one-side silicon paper. CCK papers are suitable for even the most demanding and diverse label converting processes.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	125	±2
Thickness	ILKAY 017	µm	128	±2

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.