



# TECHNICAL SPECIFICATIONS

## NOVITA® 20301 – PP Transparent / 0601 / CCK 125

### FACESTOCK

#### PP Transparent

**Description** Glossy biaxially-oriented polypropylene with printreceptive topcoating. Good temperature and chemicals resistance.

**Printing Process** Suitable for offset print.

**Applications** High quality labelling of cosmetics and parfumes where durability and resistance to moisture and chemicals are required.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m <sup>2</sup>	49	±2
Thickness	ILKAY 017	µm	50	±2

### ADHESIVE

#### 0601

**Description** General use permanent adhesive for papers and films. High initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.

**Shelf Life** Two years, stored at 22°C / 50% RH.

Property	Standart	Units	Value	Tolerance
Adhesion (Peel 90°/Steel)	ILKAY 003	N/25 mm	7	minimum
Loop Tack	ILKAY 001	N/25 mm	5	minimum
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Minimum service temperature		°C	+80	

### LINER

#### CCK 125

**Description** Good dimensional stability and layflatness, one-side silicon paper. CCK papers are suitable for even the most demanding and diverse label converting processes.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m <sup>2</sup>	125	±2
Thickness	ILKAY 017	µm	128	±2

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.